RACKS BRAX®

COMPATIBILITY POCKET GUIDE





AWNING AND ACCESSORY MODELS

CLICK OR TAP ON AN AWNING/ACCESSORY BELOW TO TAKE YOU TO THE PAGE TO FIND OUT WHAT YOU NEED

MAXTRAX® LITE	3
MAXTRAX® MINI	5
MAXTRAX® MKII	6
MAXTRAX® XTREME	8
MAXTRAX® IAXBASE	10



MAXTRAX® LITE

ITEMS REQUIRED MINIMUM FOR **FAST ON, FAST OFF!**

MOUNTING POINTS 2

HITCHES NEEDED 8159 – HD Hitch Standard AND

ALSO REQUIRED 8210 – HD Accessory Plate Gen 2;

Use where brackets **cannot be located at 634mm** centres, the distance between the centres of the recovery board mounting points. this is typical of roof rack bars or platform racks with slats/bars that run

TRANSVERSE (across the width of the vehicle); OR

8173 - HD Accessory Bars

Where brackets **can be located at 634mm** centres (typically for platform racks with slats that run **LONGITUDINAL** (along the length of the vehicle).

BRACKETS REQUIRED FOR **FAST ON, FAST OFF!**

MOUNTING POINTS 2

BRACKETS NEEDED

✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)

8300 - HD L50 L Brackets (DOUBLE)*

For vertical storage of recovery Boards on the side of vehicle.

*These Brackets can also mount to the underside of the Front Runner® Slimline II® platform (sides of the platform only-not rear) and are supplied with extra fasteners for this purpose.

Note: Some platform rack styles have limits on load carried on the outer perimeter slat/bars of North to South platforms, e.g. Rhino-Rack® Pioneer® Platform, Pioneer® Tradie and Pioneer Tray® and may require a bracket to bridge across to the inner or 2nd slat as well (see product 8306 below); OR

8304 - HD Adjustable Brackets Short (DOUBLE)**

For storing recovery boards to nominally match the rake of the side of the vehicle (15 degrees off vertical); OR

✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)

8306 – HD Adjustable Brackets Long (DOUBLE)**

For storing recovery boards to nominally match the rake of the side of the vehicle (15 degrees off vertical).

*ROOF RACKS WITH PERIMETER LIPS REQUIRE <u>PACKERS</u> TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO <u>ROOF RACK</u> GUIDE FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

[†] These brackets are both height and angle adjustable.



WALL MOUNTS OPTIONAL

ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR **BENEFITS**

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts⁺

✓ LOCKED GARAGES **✓** WORKSHOP WALLS

UNSECURED LOCATION 8161 - HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these

are for static wall use ONLY.



MAXTRAX® MINI

② SADLY NOT COMPATIBLE ②



MAXTRAX® MKII

ITEMS REQUIRED MINIMUM FOR **FAST ON, FAST OFF!**

MOUNTING POINTS 2

HITCHES NEEDED 8159 – HD Hitch Standard AND

ALSO REQUIRED 8210 – HD Accessory Plate Gen 2;

Use where brackets **cannot be located at 890mm** centres, the distance between the centres of the recovery board mounting points. this is typical of roof rack bars or platform racks with slats/bars that run

TRANSVERSE (across the width of the vehicle); OR

8173 - HD Accessory Bars

Where brackets **can be located at 890mm** centres (typically for platform racks with slats that run **LONGITUDINAL** (along the length of the vehicle).

BRACKETS REQUIRED FOR **FAST ON, FAST OFF!**

MOUNTING POINTS 2

BRACKETS NEEDED

✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)

8300 - HD L50 L Brackets (DOUBLE)*

For vertical storage of recovery Boards on the side of vehicle.

*These Brackets can also mount to the underside of the Front Runner® Slimline II® platform (sides of the platform only-not rear) and are supplied with extra fasteners for this purpose.

Note: Some platform rack styles have limits on load carried on the outer perimeter slat/bars of North to South platforms, e.g. Rhino-Rack® Pioneer® Platform, Pioneer® Tradie and Pioneer Tray® and may require a bracket to bridge across to the inner or 2nd slat as well (see product 8306 below); OR

8304 - HD Adjustable Brackets Short (DOUBLE)**

For storing recovery boards to nominally match the rake of the side of the vehicle (15 degrees off vertical); OR

✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)

8306 – HD Adjustable Brackets Long (DOUBLE)*+

For storing recovery boards to nominally match the rake of the side of the vehicle (15 degrees off vertical).

*ROOF RACKS WITH PERIMETER LIPS REQUIRE <u>PACKERS</u> TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO <u>ROOF RACK</u> GUIDE FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

[†] These brackets are both height and angle adjustable.



WALL MOUNTS OPTIONAL

BENEFITS ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts*

✓ LOCKED GARAGES
✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 - HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these

are for static wall use ONLY.



MAXTRAX® XTREME

ITEMS REQUIRED MINIMUM FOR **FAST ON, FAST OFF!**

MOUNTING POINTS 2

HITCHES NEEDED 8159 – HD Hitch Standard AND

ALSO REQUIRED 8210 – HD Accessory Plate Gen 2;

Use where brackets **cannot be located at 890mm** centres, the distance between the centres of the recovery board mounting points. this is typical of roof rack bars or platform racks with slats/bars that run

TRANSVERSE (across the width of the vehicle); OR

8173 - HD Accessory Bars

Where brackets **can be located at 890mm** centres (typically for platform racks with slats that run **LONGITUDINAL** (along the length of the vehicle).

BRACKETS REQUIRED FOR **FAST ON, FAST OFF!**

MOUNTING POINTS 2

BRACKETS NEEDED

✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)

8300 - HD L50 L Brackets (DOUBLE)*

For vertical storage of recovery Boards on the side of vehicle.

*These Brackets can also mount to the underside of the Front Runner® Slimline II® platform (sides of the platform only-not rear) and are supplied with extra fasteners for this purpose.

Note: Some platform rack styles have limits on load carried on the outer perimeter slat/bars of North to South platforms, e.g. Rhino-Rack® Pioneer® Platform, Pioneer® Tradie and Pioneer Tray® and may require a bracket to bridge across to the inner or 2nd slat as well (see product 8306 below); OR

8304 - HD Adjustable Brackets Short (DOUBLE)**

For storing recovery boards to nominally match the rake of the side of the vehicle (15 degrees off vertical); OR

✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)

8306 – HD Adjustable Brackets Long (DOUBLE)*+

For storing recovery boards to nominally match the rake of the side of the vehicle (15 degrees off vertical).

*ROOF RACKS WITH PERIMETER LIPS REQUIRE <u>PACKERS</u> TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO <u>ROOF RACK</u> GUIDE FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

[†] These brackets are both height and angle adjustable.



WALL MOUNTS OPTIONAL

BENEFITS ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts*

✓ LOCKED GARAGES
✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 - HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these

are for static wall use ONLY.

MAXTRAX

RACKSBRAX®

MAXTRAX® JAXBASE

2 SADLY NOT COMPATIBLE 2